



SAFETY DATA SHEET

6

Revision Date 28-May-2015

Version 1

1. IDENTIFICATION

Product identifier

Product Name 765-1150 NAPA LUBRIGARD ANTI-SEIZE COMPOUND (PTX81464) 8.5 OZ

Other means of identification

Product Code 21113
Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Aerosol Lubricant
Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex
10 Columbus Blvd.
Hartford, CT 06106 USA

Distributor

ITW Permatex Canada
35 Brownridge Road, Unit 1
Halton Hills, ON Canada L7G 0C6
Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex
(877) 376-2839
24 Hour Emergency Phone Number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

E-mail address mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)


| | |
|--|------------|
| Skin corrosion/irritation | Category 2 |
| Serious eye damage/eye irritation | Category 2 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Aspiration toxicity | Category 1 |
| Flammable aerosols | Category 1 |

Label elements

Emergency Overview

Danger

Causes skin irritation
Causes serious eye irritation
May cause drowsiness or dizziness
May be fatal if swallowed and enters airways
Extremely flammable aerosol



Appearance Gray

Physical state Liquid Aerosol

Odor Solvent

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
Wear eye/face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Do not spray on an open flame or other ignition source
Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
Specific treatment (see supplemental first aid instructions on this label)
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN: Wash with plenty of soap and water
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash before reuse
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Toxic to aquatic life with long lasting effects. The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346. This note applies only to certain complex oil derived substances in Annex I.

Unknown acute toxicity

17.5 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

| Chemical Name | CAS No | Weight-% | Trade Secret |
|---|------------|----------|--------------|
| ACETONE | 67-64-1 | 10 - 30 | * |
| HEPTANE | 142-82-5 | 10 - 30 | * |
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC | 64742-52-5 | 10 - 30 | * |
| CALCIUM OXIDE | 1305-78-8 | 7 - 13 | * |

| | | | |
|------------------|-----------|--------|---|
| ALUMINIUM POWDER | 7429-90-5 | 5 - 10 | * |
| GRAPHITE | 7782-42-5 | 3 - 7 | * |
| CARBON DIOXIDE | 124-38-9 | 1 - 5 | * |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

| | |
|---|--|
| General advice | Get medical advice/attention if you feel unwell. |
| Eye contact | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| Skin contact | IF ON SKIN: Wash skin with soap and water. If skin irritation persists, call a physician. Wash contaminated clothing before reuse. |
| Inhalation | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician. |
| Ingestion | IF SWALLOWED: Call a physician or poison control center immediately. Do NOT induce vomiting. |
| Self-protection of the first aider | Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. |

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO₂), Dry chemical, Foam

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Extremely flammable. Keep product and empty container away from heat and sources of ignition. Vapors may travel to source of ignition and flash back.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Contents under pressure. Do not puncture or incinerate cans.

Environmental precautions

Environmental precautions See Section 12 for additional ecological information. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.
 Methods for cleaning up Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.
 Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required. Take precautionary measures against static discharges. Do not puncture or incinerate cans. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).
 Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|-------------------------------|--|--|---|
| ACETONE 67-64-1 | STEL: 750 ppm TWA: 500 ppm | TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm | IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³ |
| HEPTANE 142-82-5 | STEL: 500 ppm TWA: 400 ppm | TWA: 500 ppm TWA: 2000 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m ³ | IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 85 ppm TWA: 350 mg/m ³ |
| CALCIUM OXIDE 1305-78-8 | TWA: 2 mg/m ³ | TWA: 5 mg/m ³ (vacated) TWA: 5 mg/m ³ not in effect as a result of reconsideration | IDLH: 25 mg/m ³ TWA: 2 mg/m ³ |
| ALUMINIUM POWDER 7429-90-5 | TWA: 1 mg/m ³ respirable fraction | TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ Al Aluminum | TWA: 5 mg/m ³ Al |

| | | | |
|----------------------------|--|---|---|
| GRAPHITE 7732-42-5 | TWA: 2 mg/m ³ respirable fraction all forms except graphite fibers | TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural | IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ natural respirable dust |
| CARBON DIOXIDE 124-38-9 | STEL: 30000 ppm TWA: 5000 ppm | TWA: 5000 ppm TWA: 9000 mg/m ³ (vacated) TWA: 10000 ppm (vacated) TWA: 18000 mg/m ³ (vacated) STEL: 30000 ppm (vacated) STEL: 54000 mg/m ³ | IDLH: 40000 ppm TWA: 5000 ppm TWA: 9000 mg/m ³ STEL: 30000 ppm STEL: 54000 mg/m ³ |

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).
Skin and body protection Wear protective gloves and protective clothing.
Respiratory protection Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid; Aerosol
Appearance Gray
Odor Solvent
Odor threshold No information available

| <u>Property</u> | <u>Values</u> | <u>Remarks • Method</u> |
|--------------------------------|--------------------------|--|
| pH | No information available | |
| Melting point / freezing point | No information available | |
| Boiling point / boiling range | No information available | |
| Flash point | < -18 °C / < 0 °F | Gives a flame projection at full valve opening or flashback at any degree of valve opening |
| Evaporation rate | No information available | |
| Flammability (solid, gas) | No information available | |
| Flammability Limit in Air | | |
| Upper flammability limit: | No information available | |
| Lower flammability limit: | No information available | |
| Vapor pressure | No information available | |
| Vapor density | >1 | Air = 1 |

| | |
|------------------------------|--------------------------|
| Relative density | 0.885-0.905 |
| Water solubility | Insoluble in water |
| Solubility in other solvents | No information available |
| Partition coefficient | No information available |
| Autoignition temperature | No information available |
| Decomposition temperature | No information available |
| Kinematic viscosity | No information available |
| Dynamic viscosity | No information available |
| Explosive properties | No information available |
| Oxidizing properties | No information available |

Other Information

| | |
|------------------|--------------------------|
| Softening point | No information available |
| Molecular weight | No information available |
| VOC Content (%) | 24.5% |
| Density | No information available |
| Bulk density | No information available |

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides
Copper compounds

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

| | |
|--------------|--|
| Inhalation | May cause irritation of respiratory tract. May cause drowsiness or dizziness. |
| Eye contact | Contact with eyes may cause irritation. May cause redness and tearing of the eyes. |
| Skin contact | May cause skin irritation and/or dermatitis. |
| Ingestion | Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis. |

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|----------------------------|----------------------|-------------------------|---------------------------------------|
| ACETONE 67-64-1 | = 5800 mg/kg (Rat) | - | = 50100 mg/m ³ (Rat) 8 h |
| HEPTANE 142-82-5 | - | = 3000 mg/kg (Rabbit) | = 103 g/m ³ (Rat) 4 h |
| CALCIUM OXIDE 1305-78-8 | = 500 mg/kg (Rat) | - | - |

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|---|-------|---------|-----|------|
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC 64742-52-5 | A2 | Group 1 | - | X |

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects Central nervous system, Central Vascular System (CVS), Eyes, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 3394 mg/kg

ATEmix (dermal) 12375 mg/kg

ATEmix (inhalation-dust/mist) 186 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

| Chemical Name | Algae/aquatic plants | Fish | Crustacea |
|---|----------------------|---|--|
| ACETONE 67-64-1 | - | 4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50 | 10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50 |
| HEPTANE 142-82-5 | - | 375.0: 96 h Cichlid fish mg/L LC50 | 10: 24 h Daphnia magna mg/L EC50 |
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC 64742-52-5 | - | 5000: 96 h Oncorhynchus mykiss mg/L LC50 | 1000: 48 h Daphnia magna mg/L EC50 |
| CALCIUM OXIDE 1305-78-8 | - | 1070: 96 h Cyprinus carpio mg/L LC50 static | - |

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

| Chemical Name | Partition coefficient |
|---------------------|-----------------------|
| ACETONE 67-64-1 | -0.24 |
| HEPTANE 142-82-5 | 4.66 |

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

| Chemical Name | RCRA | RCRA - Basis for Listing | RCRA - D Series Wastes | RCRA - U Series Wastes |
|--------------------|------|-----------------------------------|------------------------|------------------------|
| ACETONE 67-64-1 | - | Included in waste stream: F039 | - | U002 |

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name | California Hazardous Waste Status |
|-------------------------------|-----------------------------------|
| ACETONE 67-64-1 | Ignitable |
| HEPTANE 142-82-5 | Toxic Ignitable |
| CALCIUM OXIDE 1305-78-8 | Corrosive |
| ALUMINIUM POWDER 7429-90-5 | Ignitable powder |

14. TRANSPORT INFORMATION

DOT

UN/ID no 1950
 Proper shipping name: Aerosols, Limited Quantity (LQ)
 Hazard Class 2.1
 Emergency Response Guide
 Number 126

IATA

UN/ID no ID 8000
 Proper shipping name: Consumer commodity
 Hazard Class 9
 ERG Code 9L

IMDG

UN/ID no 1950
 Proper shipping name: Aerosols, Limited Quantity (LQ)
 Hazard Class 2.1
 EmS-No F-D, S-U

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL/NDSL Complies
 EINECS/ELINCS Complies
 ENCS Not Listed. Contains Natural substance(s)
 IECSC Complies
 KECL Complies
 PICCS Complies

AICS

Complies

Legend:

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS - Japan Existing and New Chemical Substances
- IECSC - China Inventory of Existing Chemical Substances
- KECL - Korean Existing and Evaluated Chemical Substances
- PICCS - Philippines Inventory of Chemicals and Chemical Substances
- AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name | SARA 313 - Threshold Values % |
|------------------------------|-------------------------------|
| ALUMINIUM POWDER - 7429-90-5 | 1.0 |

SARA 311/312 Hazard Categories

| | |
|-----------------------------------|-----|
| Acute health hazard | Yes |
| Chronic Health Hazard | No |
| Fire hazard | Yes |
| Sudden release of pressure hazard | No |
| Reactive Hazard | No |

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical Name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|--------------------|--------------------------|----------------|--|
| ACETONE 67-64-1 | 5000 lb | - | RQ 5000 lb final RQ RQ 2270 kg final RQ |

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|-------------------------------|------------|---------------|--------------|
| ACETONE 67-64-1 | X | X | X |
| HEPTANE 142-82-5 | X | X | X |
| CALCIUM OXIDE 1305-78-8 | X | X | X |
| ALUMINIUM POWDER 7429-90-5 | X | X | X |
| GRAPHITE 7782-42-5 | X | X | X |
| CARBON DIOXIDE 124-38-9 | X | X | X |

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

| | | | | |
|-------------|------------------|----------------|--------------------|-----------------------|
| <u>NFPA</u> | Health hazards 2 | Flammability 4 | Instability 0 | - |
| <u>HMIS</u> | Health hazards 2 | Flammability 4 | Physical hazards 0 | Personal protection 5 |

NFPA (National Fire Protection Association)
HMIS (Hazardous Material Information System)

Revision Date 23-May-2015

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet