

FRAZEE PAINT & WALLCOVERINGS -- MAJESTIC (ALL COLORS), 002 -- 8010-00N058796

===== Product Identification =====

Product ID:MAJESTIC (ALL COLORS), 002
MSDS Date:07/12/1990
FSC:8010
NIIN:00N058796
MSDS Number: BXDMY
=== Responsible Party ===
Company Name:FRAZEE PAINT & WALLCOVERINGS
Address:6625 MIRAMAR RD
City:SAN DIEGO
State:CA
ZIP:92121
Country:US
Info Phone Num:619-276-9500
Emergency Phone Num:619-543-6000
Preparer's Name:ZEKE
CAGE:F0493

=== Contractor Identification ===
Company Name:FRAZEE INDUSTRIES INC
Address:6625 MIRAMAR RD
City:SAN DIEGO
State:CA
ZIP:92121
Country:US
Phone:858-626-3600
CAGE:1GK99
Company Name:FRAZEE PAINT & WALL COVERINGS
Address:6625 MIRAMAR ROAD
City:SAN DIEGO
State:CA
ZIP:92121
Phone:(619) 276-9500
CAGE:F0493

===== Composition/Information on Ingredients =====

Ingred Name:SILICA, CRYSTALLINE - QUARTZ; (SILICON DIOXIDE)
CAS:14808-60-7
RTECS #:VV7330000
Fraction by Wt: 8.09%
OSHA PEL:SEE TABLE Z-3
ACGIH TLV:0.1 MG/M3 RDUST

Ingred Name:ETHYLENE GLYCOL (SARA 313) (CERCLA) VP:0.1 @ 68F
CAS:107-21-1
RTECS #:KW2975000
Fraction by Wt: 1%
OSHA PEL:N/K
ACGIH TLV:C 50 PPM,VAPOR
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:COATING VOLATILE ORGANIC COMPOUND:0.63 LB/GL (76 G/L).
RTECS #:9999999V0
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:MATERIAL VOLATILE ORGANIC COMPOUND:0.27 LB/GL (33G/L)
RTECS #:9999999V0
OSHA PEL:N/K
ACGIH TLV:N/K

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
 Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
 Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
 Health Hazards Acute and Chronic:INHALATION:IF THERE ARE SIGNS OF
 OVEREXP TO VAP/MIST CAN CAUSE HDCH, NAUS & IRRIT OF NOSE, THROAT &
 LUNGS. SKIN/EYE:USE GOOD PERSONAL HYGIENE PRACT WHILE WORKING
 W/MATL. DRY CONTAM CLTHG BEFORE REUSE. INGEST:MAY BE HARMFUL. MAY
 CAUSE NAUS,VOMIT, DIARR & GI IRRIT. CONSULT MD.
 Explanation of Carcinogenicity:SILICA, CRYSTALLINE-QUARTZ:IARC
 MONOGRAPHS, SUPP. VOL 7, PG 341, 1987:GROUP 2A. NTP 7TH ANNUAL RPT
 ON CARCINS. (SUPDAT)
 Effects of Overexposure:SEE HEALTH HAZARDS.
 Medical Cond Aggravated by Exposure:OVEREXPOSURE TO VAPORS CAN CAUSE
 HEADACHES, DIZZINESS AND NAUSEA.

===== First Aid Measures =====

First Aid:SKIN:CLEAN WITH SOAP AND WATER. INGESTION:CONSULT A
 PHYSICIAN. INHALATION:REMOVE TO FRESH AIR. EYE:FLUSH WITH WATER FOR
 AT LEAST 15 MINUTES. CONSULT A PHYSICIAN.

===== Fire Fighting Measures =====

Lower Limits:3.2%
 Extinguishing Media:FOAM, ALCOHOL FOAM, CO*2, DRY CHEMICAL, WATER FOG.
 Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL
 PROTECTIVE EQUIPMENT . FOLLOW RECOMMENDED PROCEDURES IN HANDLING
 FIRE AREAS.
 Unusual Fire/Explosion Hazard:POLYMER FILM CAN BURN. MATERIAL CAN
 SPLATTER ABOVE 212F.

===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP IMMEDIATELY AND SAFELY DISCARD
 ABSORBENTS. IN THE EVENT OF LARGE SPILLS, DIKE THE AREA AND PUMP
 THE MATERIAL TO AN EPA PERMITTED WASTE TANK.
 Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:USE WITH ADEQUATE VENTILATION. AVOID
 PROLONGED BREATHING OF VAPOR. AVOID PROLONGED OR REPEATED SKIN
 CONTACT. KEEP AWAY FROM EXCESSIVE HEAT.
 Other Precautions:AVOID ALL SOURCES OF HEAT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHEN SPRAYING MATL, USE NIOSH/MSHA APPRVD
 CARTRIDGE RESP/GAS MASK SUITABLE TO KEEP AIRBORNE MISTS & VAP CONC
 BELOW TIME WEIGHTED TLVS. WHEN USING IN POORLY VENT & CONFINED
 SPACE USE NIOSH/MSHA APPRVD FRESH-AIR SUPPLYING RESP/SCBA.
 Ventilation:MAINTAIN GOOD VENTILATION TO KEEP PRODUCT VAPOR
 CONCENTRATIONS BELOW SPECIFIED TLV VALUES.
 Protective Gloves:IMPERVIOUS GLOVES .
 Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS .
 Other Protective Equipment:ANSI APPROVED EYE WASHES AND SAFETY SHOWERS
 IN THE WORKPLACE ARE RECOMMENDED. TO PVNT RPTD/PRLNGD SKIN CONTACT
 (SUP DAT)
 Work Hygienic Practices:BARRIER CREAMS AND DAILY SHOWERS AND CHANGE OF
 CLOTHES ARE RECOMMENDED.
 Supplemental Safety and Health
 EXPLAN OF CARCIN:1994:ANTICIPATED TO BE CARCINOGENIC. OTHER PROT

EQUIP:IMPERVIOUS CLOTHING AND BOOTS.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C
Vapor Pres:SEE INGS
Vapor Density:LTR/AIR
Spec Gravity:1.4 (H*20=1)
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:DILUTABLE
Appearance and Odor:WHITE VISCOUS LIQUID, MILD ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID MATERIALS THAT ARE WATER REACTIVE. ALSO AVOID STRONG ALKALINE AND
ACIDIC SUBSTANCES.
Stability Condition to Avoid:EXCESS HEAT MAY CAUSE CONTAINERS TO
RUPTURE. AVOID TEMPERATURES BELOW 40F. AVOID FREEZING CONDITIONS.
Hazardous Decomposition Products:CO, CO*2 ON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS CURRENTLY IN FORCE FOR THIS PRODUCT HAZARD
CLASS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.