

Section 1 Chemical Product and Company Identification

Page E1 of E2



5100 West Henrietta Rd
PO Box 92912
Rochester, NY 14692-9012
Tel: (800) 962-2660

Boreal Science
399 Vansickle Road
St. Catharines, Ontario
L2S 3T4 Canada
Tel: (800) 387-9393

CHEMTREC 24 Hour Emergency USA
Phone Number (800) 424-9300
For laboratory and industrial use only.
Not for drug, food or household use.

Product PETROLEUM ETHER**Synonyms** Ligroin / VM&P Naphtha

Section 2 Hazards Identification

Signal word: DANGER**Pictograms:** GHS02 / GHS08**Target organs:** Central nervous system**GHS Classification:**

Flammable liquid (Category 2)

Aspiration hazard (Category 1)

Mutagenicity (Category 1B)

Carcinogenicity (Category 1B)

GHS Label information: Hazard statement:

H225: Highly flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H340: May cause genetic defects.

H350: May cause cancer.

Precautionary statement:

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233: Keep container tightly closed.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310+P331: IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P308+P313: IF exposed or concerned: Get medical attention.

P370+P378: In case of fire: Use dry chemical, alcohol foam, carbon dioxide to extinguish.

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

P501: Dispose of contents/container to a licensed chemical disposal agency in accordance with local/regional/national regulations.

Hazards not otherwise classified:

Health hazards not otherwise classified (HHNOC) - Repeated exposure may cause skin dryness or cracking.

Physical hazards not otherwise classified (PHNOC) - Not Known

Section 3 Composition / Information on Ingredients

Chemical Name	CAS #	%	EINECS
Petroleum ether	8032-32-4	100%	232-453-7

Section 4 First Aid Measures

INGESTION: MAY BE HARMFUL OR FATAL IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.**INHALATION:** MAY BE HARMFUL IF INHALED. MAY CAUSE RESPIRATORY TRACT IRRITATION. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.**EYE CONTACT:** MAY CAUSE EYE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.**SKIN ABSORPTION:** MAY BE HARMFUL IF ABSORBED THROUGH SKIN. MAY CAUSE SKIN IRRITATION. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Section 5 Fire Fighting Measures

Suitable Extinguishing Media: Carbon dioxide, dry chemical, dry sand, alcohol foam.**Protective Actions for Fire-fighters:** In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep fire-exposed containers cool.**Specific Hazards:** During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Vapor may cause flash fire. Dangerous fire hazard when exposed to heat or flame. Vapors can flow along surfaces to distant ignition source and flash back. Contact with strong oxidizers may cause fire.

Section 6 Accidental Release Measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.**Environmental Precautions:** Avoid runoff into storm sewers and ditches which lead to waterways.**Containment and Cleanup:** Remove all sources of ignition. Absorb with inert dry material, sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale vapors, spray or mist. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, dry, well-ventilated area away from incompatible substances. Keep away from ignition sources.

Section 8 Exposure Controls / Personal Protection

Exposure Limits:	Chemical Name	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)
	VM&P Naphtha	Not established	Not established	TWA: 350 mg/m ³ STEL: C1800 mg/m ³

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If misty conditions prevail, work in fume hood or wear a NIOSH/MSHA-approved respirator.

Section 9 Physical & Chemical Properties

Appearance: Clear, colorless liquid. Odor: Gasoline or kerosene-like odor. Odor threshold: Data not available. pH: Data not available. Melting / Freezing point: <-73°C (-99°F) Boiling point: 20-75°C (68-167°F) Flash point: -18°C (0.4°F) CC	Evaporation rate (Butyl acetate = 1): Ca 10 Flammability (solid/gas): Data not available. Explosion limits: Lower / Upper: 1.1% / 5.9% Vapor pressure (mm Hg): Ca 40 @ 20°C (68°F) Vapor density (Air = 1): 2.5 Relative density (Specific gravity): 0.60-0.75 Solubility(ies): Insoluble in water.	Partition coefficient: Data not available Auto-ignition temperature: 288°C (550°F) Decomposition temperature: Data not available. Viscosity: Data not available. Molecular formula: Mixture Molecular weight: Mixture
--	---	--

Section 10 Stability & Reactivity

Chemical stability: Stable **Hazardous polymerization:** Will not occur.
Conditions to avoid: Heat and sunlight can cause instability. Avoid heat, flame, ignition sources, sunlight and incompatibles.
Incompatible materials: Strong oxidizers. Will attack some forms of plastics, rubber and coatings.
Hazardous decomposition products: Oxides of carbon.

Section 11 Toxicological Information

Acute toxicity: Inhalation-rat LC50: 3400 ppm/4 hours
Skin corrosion/irritation: Data not available
Serious eye damage/irritation: Data not available
Respiratory or skin sensitization: Data not available
Germ cell mutagenicity: Data not available
Carcinogenicity: Data not available
 NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
 IARC classified: Group 3: Not classifiable as to its carcinogenicity to humans. [Petroleum solvents]
 OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
Reproductive toxicity: Data not available
STOT-single exposure: Data not available
STOT-repeated exposure: Data not available
Aspiration hazard: Data not available
Potential health effects:
 Inhalation: Inhalation of this material may cause symptoms of intoxication and peripheral nerve disorders and central nervous system depression. Symptoms of overexposure include loss of appetite, muscle weakness, impairment of motor action, dizziness and drowsiness. May also cause throat irritation.
 Ingestion: Ingestion will cause burning sensation in mouth, esophagus, and stomach. Vomiting, blurred vision, and diarrhea may also occur. Cases of chemical pneumonia have been reported from ingestion of this substance. Nervous system disorders paralleling those from inhalation exposure may also occur.
 Skin: Contact with skin causes irritation defatting on prolonged contact.
 Eyes: Contact with eyes may cause redness and pain. Vapors may cause irritation.
Signs and symptoms of exposure: Exercise appropriate procedures to minimize potential hazards.
Additional information: RTECS #: OI6180000

Section 12 Ecological Information

Toxicity to fish: No data available
Toxicity to daphnia and other aquatic invertebrates: No data available
Toxicity to algae: Selenastrum capricornutum (Algae) EC50: 4700 mg/L/72 hours (growth rate)
Persistence and degradability: No data available **Bioaccumulative potential:** No data available
Mobility in soil: No data available **PBT and vPvB assessment:** No data available
Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Section 13 Disposal Considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Section 14 Transport Information (US DOT / CANADA TDG)

UN/NA number: UN1268 **Shipping name:** Petroleum distillates, n.o.s., (Petroleum ether)
Hazard class: 3 **Packing group:** II **Reportable Quantity:** No **Marine pollutant:** No
Exceptions: Limited quantity equal to or less than 1 L **2016 ERG Guide #** 128

Section 15 Regulatory Information

A chemical is considered to be listed if the CAS number for the anhydrous form is on the Inventory list.

Component	TSCA	CERCLA (RQ)	RCRA code	DSL	NDSL	CA Prop 65
Petroleum ether	Listed	Not listed	D001	Listed	Not listed	This product does not contain any chemicals known to the State of California to cause cancer or reproductive toxicity.

Section 16 Other Information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook.